

Certificate no: CMNZ10019

Version: Revision 3

Original issue date: 15 May 2020

Version date: 7th February 2025

1. Certificate Holder Details



Hiandri Ltd
PO Box 819,
Christchurch, 8140
Tel: 021 611 290
Email: sales@hiandri.com
Web: hiandri.com

2. Product Certification Body

BRANZ Limited
1222 Moonshine Rd,
RD1, Porirua 5381
Private Bag 50 908,
Porirua 5240, New Zealand
Tel: 04 237 1170
Email: assuranceservices@branz.co.nz
Web: branz.nz

Complaints: The complaints process for this certificate can be found here:

<https://www.branz.co.nz/codemark-info/complaints-and-appeals/>

Product Certificate

HIANDRI BOTTOM PLATE PACKERS

3. Description of Building Method or Product

Hiandri Bottom Plate Packers provide a 12 mm gap under the bottom plate of light weight timber framing to allow for unimpeded drainage of water from floors during construction. The packers are manufactured from polypropylene plastic with a plan dimension of 84 x 60 mm and are labelled on the underside with the product name.

4. Intended use of Building Method or Product

- Hiandri Bottom Plate Packers are used for separating the bottom plates of internal and external walls from concrete floor slabs or from timber flooring in timber-framed buildings, to allow for unimpeded drainage of water from floors during construction.
- This Product Certificate covers the use of Hiandri Bottom Plate Packers in buildings otherwise designed and constructed in accordance with NZS 3604. The use of Hiandri Bottom Plate Packers with steel-framed buildings or under fire or acoustically rated walls is outside the scope of certification.

5. New Zealand Building Code Provisions

Clause B1 STRUCTURE: Performance B1.3.1, B1.3.2 and B1.3.4. Hiandri Bottom Plate Packers meet the requirements for loads arising from self-weight, imposed gravity loads arising from use, earthquake, snow and wind [i.e. B1.3.3 (a), (b), (f), (g) and (h)].

Clause B2 DURABILITY: Performance B2.3.1 (a) not less than 50 years and B2.3.2.

Clause E2 EXTERNAL MOISTURE: Performance E2.3.3.

Clause F2 HAZARDOUS BUILDING MATERIALS: Performance F2.3.1.

5A. CONTRIBUTES TO THE FOLLOWING PROVISIONS OF THE NZBC:

Clause H1 ENERGY EFFICIENCY: Performance H1.3.1 and H1.3.2E.

6. Conditions and Limitations of Use

- Hiandri Bottom Plate Packers must be used in accordance with Hiandri Ltd's Reference Documents.
- Hiandri Bottom Plate Packers may also be used with fire rated and/or acoustically rated walls, however this has not been assessed and is outside the scope of this Product Certification.



This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004. This certificate may only be reproduced in its entirety. It is advised to check that this certificate is currently valid and not withdrawn or suspended by referring to the Register of Product Certificates on the Building Performance website <http://www.building.govt.nz>.

Certificate no: CMNZ10019

Version: Revision 3

Original issue date: 15 May 2020

Version date: 7th February 2025

Product Certificate

HIANDRI BOTTOM PLATE PACKERS



- Studs under girder trusses supporting a tributary roof area greater than 36 m² and up to 50 m² require two packers. Where a girder truss with a tributary roof area greater than 20 m² and a mid-floor lintel coincide, three packers are required under the lower storey studs supporting the mid-floor lintel.
- An air seal complying with NZBC Acceptable Solution E2/AS1, Paragraph 9.1.6 c) or covered by a valid BRANZ Appraisal must be installed to all exterior walls, including first floor exterior walls, after the framing is erected and before the framing is closed in by external claddings and internal linings.

Reference Documents

This Product Certificate must be used in accordance with:

- Installation Manual for Hiandri Bottom Plate Packer, V.7, dated December 2024.

7. Health and Safety Information

Care must be taken in factory when fixing the Hiandri packers to the bottom plates.

8. Basis for Certification

The following tests have been carried out on Hiandri Bottom Plate Packers:

- Comprehensive strength tests have been carried out on Hiandri Bottom Plate Packers by independent laboratories. The results of these tests have been reviewed by BRANZ and found to be satisfactory.
- BRANZ Expert Judgement (Structural Engineer) confirmation of compliance to the NZBC Clause B1 Structure Performance Requirements.
- BRANZ Expert Judgement (Materials Scientist) confirmation of compliance to the NZBC Clause B2 Durability Performance Requirements.
- BRANZ Expert Judgement (Building Physicist) confirmation of contribution to compliance to the NZBC Clause H1 Energy Efficiency Performance Requirements.
- The practicability of installation of Hiandri Bottom Plate Packers has been assessed by BRANZ and found to be satisfactory.
- The referenced Reference Document has been examined by BRANZ and found to be satisfactory.
- The quality of supply to the market is the responsibility of Hiandri Ltd.
- Building contractors are responsible for the incorporation of Hiandri Bottom Plate Packers in accordance with the instructions of Hiandri Ltd.

9. Supporting Documentation for Certification

- BRANZ Appraisal No. 1095 Hiandri Bottom Plate Packers.



This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004. This certificate may only be reproduced in its entirety. It is advised to check that this certificate is currently valid and not withdrawn or suspended by referring to the Register of Product Certificates on the Building Performance website <http://www.building.govt.nz>.

Certificate no: CMNZ10019

Version: Revision 3

Original issue date: 15 May 2020

Version date: 7th February 2025

Product Certificate

HIANDRI BOTTOM PLATE PACKERS



- BRANZ Structural Memorandum TP12394, issue date 12 March 2020. The Hiandri Bottom Plate Packers have been assessed to meet the relevant NZBC structural requirements.
- BRANZ Durability Opinion TP11943-001, issue date 6 January 2020. The Hiandri Bottom Plate Packers have been assessed to meet the relevant NZBC durability requirements.
- BRANZ Weathertightness Opinion TP12394-01, issue date 23 March 2020. The Hiandri Bottom Plate Packers have been assessed to meet the relevant NZBC weathertightness requirements.
- NZS 3604:2011 Timber-framed buildings.
- Ministry of Business, Innovation and Employment Record of amendments - Acceptable Solutions, Verification Methods and handbooks.
- The Building Regulations 1992.

10. Supporting Information About Description

Type and Intended Use of Product

- Hiandri Bottom Plate Packers are used for separating the bottom plates of internal and external walls from concrete floor slabs or from timber flooring in timber-framed buildings, to allow for unimpeded drainage of water from floors during construction.
- This Product Certificate covers the use of Hiandri Bottom Plate Packers in buildings otherwise designed and constructed in accordance with NZS 3604. The use of Hiandri Bottom Plate Packers with steel-framed buildings or under fire or acoustically rated walls is outside the scope of this Product Certification.

Description of Product

- Hiandri Bottom Plate Packers provide a 12 mm gap under the bottom plate of light weight timber framing to allow for unimpeded drainage of water from floors during construction. The packers are manufactured from polypropylene plastic with a plan dimension of 84 x 60 mm and are labelled on the underside with the product name.

Product Specification

Components supplied by Hiandri Ltd are:

- Hiandri Bottom Plate Packers - manufactured from polypropylene plastic, measuring 84 x 60 x 12 mm and coloured blue.

Components supplied by the building contractor are:

- Fixings - Hiandri Bottom Plate Packers may be fixed to the bottom plate at the pre-cut stage, hand-nailed on-site with a clout, or fixed with a brad by a finishing gun.
- Air seal - self-expanding moisture cure polyurethane foam complying with NZBC Acceptable Solution E2/AS1, Paragraph 9.1.6 c) or covered by a valid BRANZ Appraisal and installed in accordance with the Reference Document.
- Proprietary bottom plate fixings - in accordance with NZS 3604 or the Reference Document.



This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004. This certificate may only be reproduced in its entirety. It is advised to check that this certificate is currently valid and not withdrawn or suspended by referring to the Register of Product Certificates on the Building Performance website <http://www.building.govt.nz>.

Certificate no: CMNZ10019

Version: Revision 3

Original issue date: 15 May 2020

Version date: 7th February 2025

Product Certificate

HIANDRI BOTTOM PLATE PACKERS



- Proprietary bottom plate fixings for bracing elements - in accordance with the Reference Document.

11. Supporting Information About Intended Use

Installation Requirements

- Installation of Hiandri Bottom Plate Packers must be in accordance with the Hiandri Ltd Reference Documents.
- The Hiandri Bottom Plate Packers are installed to the underside of the bottom plate prior to the erection of the structural framing of the wall.
- The orientation of the Hiandri Bottom Plate Packers is dependent on the slab overhang and the size of the bottom plate. Refer to the Reference Document for the suitable orientation of the Hiandri Bottom Plate Packers for the individual design of the building.
- An air seal complying with NZBC Acceptable Solution E2/AS1, Paragraph 9.1.6 c) or covered by a valid BRANZ Appraisal must be installed to all exterior walls, including first floor exterior walls, after the framing is erected and before the framing is closed in by external claddings and internal linings.

Building Code

B1 Structure

- Double Hiandri Bottom Plate Packers are required under any supporting stud with a lintel with a span of 1,400 mm or greater.
- Triple Hiandri Bottom Plate Packers are required for use under any stud supporting a lintel with a span greater than 4,000 mm and up to 6,000 mm.
- Studs under girder trusses supporting a tributary roof area greater than 36 m² and up to 50 m² require a double packer. Where a girder truss with a tributary roof area greater than 20 m² and a mid-floor lintel coincide, a triple packer is required under the lower storey studs supporting the mid-floor lintel.
- Hiandri Bottom Plate Packers may be fixed to the bottom plate at the pre-cut stage, hand-nailed on-site with clouts or fixed with brads by a finishing gun. Additional packers may be slipped underneath the bottom plate if required and do not have to be fixed in place.
- On 140 x 45 mm frames, two Hiandri Bottom Plate Packers are required, side by side under each stud.

Bottom Plate Fixings

- Fixings used for bottom plates must meet the requirements of Paragraph 7.5.12 of NZS 3604:2011 when used with Hiandri Bottom Plate Packers.

Bracing

- Hiandri Bottom Plate Packers have been evaluated to not reduce the effectiveness of proprietary bracing systems. Refer to the Reference Document for compatible proprietary bracing systems. The compliance of proprietary bracing systems to the relevant NZBC Clauses is outside of the scope of this certification.



This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004. This certificate may only be reproduced in its entirety. It is advised to check that this certificate is currently valid and not withdrawn or suspended by referring to the Register of Product Certificates on the Building Performance website <http://www.building.govt.nz>.

Certificate no: CMNZ10019

Version: Revision 3

Original issue date: 15 May 2020

Version date: 7th February 2025

Product Certificate

HIANDRI BOTTOM PLATE PACKERS



B2 Durability

- The durable life of Hiandri Bottom Plate Packers is at least 50 years.

C3 Prevention of Fire Occurring

- Separation or protection must be provided to Hiandri Bottom Plate Packers from heat sources such as fireplaces, heating appliances and chimneys. Part 7 of NZBC Acceptable Solutions C/AS1 and NZBC Acceptable Solution C/AS2 provide methods for separation and protection of combustible materials from heat sources.

E2 External Moisture

- Hiandri Bottom Plate Packers can be used for compliance with NZS 3604:2011, Paragraph 2.3.3 (a) requiring separation between framing timbers and concrete. Air seals must be installed to all exterior frames when using Hiandri Bottom Plate Packers. The air seal must be a self-expanding polyurethane foam complying with NZBC Acceptable Solution E2/AS1, Paragraph 9.1.6 (c) and installed with the instructions of Hiandri Ltd's Reference Document.

H1 Energy Efficiency

- The 12 mm gap created by Hiandri Bottom Plate Packers must be sealed with a self-expanding polyurethane foam complying with either NZBC Acceptable Solution E2/AS1, Paragraph 9.1.6 c) or covered by a valid BRANZ Appraisal for use around window, door and other wall penetration openings.
- The Hiandri Bottom Plate Packers when installed in accordance with the Reference Document and this Product Certificate will not impact on the thermal performance of the wall.

12. Supporting Information About Conditions and Limitations of Use

All conditions and limitations provided as stated in this Product Certificate.



This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004. This certificate may only be reproduced in its entirety. It is advised to check that this certificate is currently valid and not withdrawn or suspended by referring to the Register of Product Certificates on the Building Performance website <http://www.building.govt.nz>.

Certificate no: CMNZ10019

Version: Revision 3

Original issue date: 15 May 2020

Version date: 7th February 2025

Product Certificate

HIANDRI BOTTOM PLATE PACKERS



Signatures

A handwritten signature in black ink that reads "Falck".

Claire Falck

Chief Executive Officer

BRANZ Limited

All CodeMark certificates that are current must be registered with MBIE. MBIE maintains a register of valid product certificates. [Please find the register here.](#)

If the certificate is not listed on this register or it appears as (SUSPENDED), it is not a valid CodeMark certificate and does not have to be accepted by a building consent authority as establishing compliance with the New Zealand Building Code.



This certificate is issued by an independent certification body accredited by JAS-ANZ, the product certification body appointed by the Chief Executive of the Ministry of Business, Innovation and Employment under the Building Act 2004. This certificate may only be reproduced in its entirety. It is advised to check that this certificate is currently valid and not withdrawn or suspended by referring to the Register of Product Certificates on the Building Performance website <http://www.building.govt.nz>.